Global Caché
Global Connect

OPEN API/OPEN SYSTEMS
FUTURE PROOF
WIRED, POE, 2 PORT ETHERNET SWITCH
CLOUD CONNECTED - TRUE IOT
MODULAR
SERIAL, IR, RELAY, SENSOR, HDMI, RASPBERRY PI
SCALABLE
BACKWARDS COMPATIBLE

DATA SHEET - GCIR3

GLOBAL CONNECT

IR & Sensor Module GCIR3

CONNECT. COMMAND. CONTROL.

UNPARALLELED CONNECTIVITY

Global Connect is the next generation for IP connectivity and control. With options for connecting serial, IR, relay, and HDMI switching to the network, it is easier that ever to manage and deploy equipment and have an easy method to control those devices. Utilizing the Raspberry Pi (an open source computer) when needed will provide additional options for customization and interface, including cloud connectivity. Global Connect provides a scalable solution with unlimited possibilities. If you need to connect to it, you only need one solution. Connect globally with Global Connect.

INNOVATION THROUGH AUTOMATION

3 IR outputs or sensor inputs. The GCIR3 is a 3 port IR and sensor module that connects IR devices to a wired ethernet or WiFi network when used with a Global Connect Chassis. The GCIR3 module includes three selectable 3.5mm stereo jack ports providing 3 selectable independent IR outputs or 3 independent selectable sensor inputs. IR ports support emitters and blasters. Each GCIR3 module includes built in IR learning. The GCIR3 can be combined with other GC modules in any configuration up to 10 module slots. The GCIR3 populates 1 chassis slot.

INFINITE POSSIBILITIES

7 Chassis Options	19” Rack Mount option, and 15”, 10.5”, 7.5”, 6”, and 4.5” free standing options
Networking Modules	GC-IP: 1 slot; single RJ45 10/100 ethernet connection GC-IP2: 2 slots; 2 ports RJ45 10/100 ethernet switch (required with Raspberry Pi) GC-IP-P: 2 slots; 1 port RJ45 10/100 PoE (802.3af) connection GC-IP2-P: 2 slots; 2 RJ45 10/100 ethernet switch. Port 2 is PoE enabled, Port 1 is standard ethernet
Connectivity Modules	IR, Serial, Contact Closure, Sensor, HDMI, Raspberry Pi

GLOBAL CONNECT

DATA SHEET - GCIR3

CONNECT ANY DEVICE TO A NETWORK.

GCIR3 MODULE FEATURES

3 independent selectable 3.5 stereo jack IR outputs or sensor inputs.

Individual IP address for true IoT

Integrated web server for easy configuration

Built-in IR learning (full range 20KHz to 500KHz)

Downloadable iLearn software facilitates capture and playback of IR commands

Includes 3 IR emitters and 1 IR blaster

3 blinking LEDs to indicate activity

Requires 1 module slot

Blaster support (port 3)

Supports Global Cache' video (IT-SV1), voltage (IT-SP1), and contact closure (IT-SC1) sensors

Two year limited warranty

Support available via phone, email, and portal

Global Caché

160 East California Street
PO Box 1659
Jacksonville, OR 97530

www.globalcache.com

541.899.4800 tel
541.899.4808 fax

© 2018 Global Caché, Inc. All Rights Reserved. All brand names, products, and trademarks are property of their respective owners. Information subject to change without notice. DN: 060917-01 ver. 1. Printed on recycled paper with soy inks.